


TIGER Neo

54HL4-B

420-440 Watt

ALL BLACK MONO-FACIAL MODULE



N-type



N-type Technology

N-type modules with Tunnel Oxide Passivating Contacts (TOPcon) technology offer lower LID/LeTID degradation and better low light performance.



Durability Against Extreme Environment

High salt mist and ammonia resistance.



SMBB Technology

Better light trapping and current collection to improve module power output and reliability.



HOT 3.0 Technology

N-type modules with JinkoSolar's HOT 3.0 technology offer better reliability and efficiency.




Mechanical Load Enhanced

Certified to withstand:
5400Pa front side max static test load
2400 Pa rear side max static test load



Anti-PID guarantee

Minimizes the chance of degradation caused by PID phenomena through optimization of cell production technology and material control.



25 Year
Product Warranty

30 Year
Linear Power
Warranty

1%
First-year
Degradation

0.40%
Annual Degradation
Over 30 Years

- IEC61215:2021 / IEC61730:2023
- IEC61701 / IEC62716 / IEC60068 / IEC62804
- ISO9001:2015: Quality Management System
- ISO14001:2015: Environment Management System
- ISO45001:2018: Occupational health and safety management systems



JKM420-440N-54HL4-B-F2C1-US

54HL4-B 420-440 Watt

Mechanical Characteristics

Cell Type	N -type Mono-crystalline
No. of cells	108 (54×2)
Dimensions	1722×1134×35 mm
Weight	21.0 kg
Front Glass	3.2mm, Anti-reflection Coating, High Transmission, Low Iron, Tempered Glass
Frame	Anodized Aluminium Alloy
Junction Box	IP68 Rated
Protection Class	Class II
IEC Fire Type	Class C
Connector Type	JK03M/MC4/Others
Output Cables	4.0 mm ² (+): 400 mm , (-): 200 mm or Customized Length

Packaging Configuration

Pallet Dimensions	1752×1120×1249 mm
Packing detail (Two pallets=One stack)	31 pcs/pallets, 62 pcs/stack, 806 pcs/ 40'HQ Container

Specifications (STC)


Maximum Power – Pmax [Wp]	420	425	430	435	440
Maximum Power Voltage – Vmp [V]	32.16	32.37	32.58	32.78	32.99
Maximum Power Current – Imp [A]	13.06	13.13	13.20	13.27	13.34
Open-circuit Voltage – Voc [V]	38.74	38.95	39.16	39.36	39.57
Short-circuit Current – Isc [A]	13.51	13.58	13.65	13.72	13.80
Module Efficiency STC [%]	21.51	21.76	22.02	22.28	22.53
Power Tolerance	0 ~ + 3 %				
Temperature Coefficients of Pmax	-0.29 %/°C				
Temperature Coefficients of Voc	-0.25 %/°C				
Temperature Coefficients of Isc	0.045 %/°C				

STC: Irradiance 1000W/m², Cell Temperature 25°C, AM=1.5

Application Conditions

Operating Temperature	-40 °C ~ +70°C
Maximum System Voltage	1000 VDC (IEC)
Maximum Series Fuse Rating	25 A


Engineering Drawings



*Note: For specific dimensions and tolerance ranges, please refer to the corresponding detailed module drawings.

Electrical Performance

Power-Voltage Curves (54HL4-B 430W)



Current-Voltage Curves (54HL4-B 430W)

